

Compact All In Ydelsestabel

Beregningfaktor
per meter radiator

ved 75/65/20 °C

i henhold til EN442

Ligning: $\phi = K_M \times \Delta T^n$

EN442 (W) 70/40/20°C

EN442 (W) 60/30/20°C

EN442 (W) 75/65/20°C

Højde 300				
Type	11	21	22	33
400	127	185	245	338
	81	119	157	217
	204	298	393	540
500	159	232	306	422
	102	148	196	271
	255	373	491	675
600	191	278	367	507
	122	178	235	326
	305	447	589	809
700	222	325	428	591
	143	207	274	380
	356	522	687	944
800	254	371	489	675
	163	237	313	434
	407	596	786	1.079
900	286	417	551	760
	183	267	352	488
	458	671	884	1.214
1000	318	464	612	844
	204	296	392	543
	509	745	982	1.349
1100	349	510	673	929
	224	326	431	597
	560	820	1.080	1.484
1200	381	556	734	1.013
	244	356	470	651
	611	894	1.178	1.619
1400	445	649	857	1.182
	285	415	548	760
	713	1.043	1.375	1.889
1600	508	742	979	1.351
	326	474	627	868
	814	1.192	1.571	2.158
1800	572	835	1.101	1.520
	367	534	705	977
	916	1.341	1.768	2.428
2000	635	927	1.224	1.689
	407	593	783	1.085
	1.018	1.490	1.964	2.698
2200	699	1.020	1.346	1.858
	448	652	861	1.194
	1.120	1.639	2.160	2.968
2400	762	1.113	1.468	2.026
	489	711	940	1.302
	1.222	1.788	2.357	3.238
2600	826	1.205	1.591	2.195
	529	771	1.018	1.411
	1.323	1.937	2.553	3.507
2800	890	1.298	1.713	2.364
	570	830	1.096	1.520
	1.425	2.086	2.750	3.777
3000	953	1.391	1.836	2.533
	611	889	1.175	1.628
	1.527	2.235	2.946	4.047

Højde 400				
Type	11	21	22	33
400	169	237	310	428
	109	152	198	275
	270	382	498	684
500	212	297	387	535
	136	189	248	343
	338	477	623	856
600	254	356	465	642
	163	227	297	412
	406	572	747	1.027
700	296	415	542	749
	191	265	347	481
	473	668	872	1.198
800	339	474	620	856
	218	303	396	549
	541	763	996	1.369
900	381	534	697	963
	245	341	446	618
	608	859	1.121	1.540
1000	423	593	775	1.070
	272	379	496	687
	676	954	1.245	1.711
1100	466	652	852	1.177
	300	417	545	755
	744	1.049	1.370	1.882
1200	508	712	930	1.284
	327	455	595	824
	811	1.145	1.494	2.053
1400	593	830	1.085	1.498
	381	530	694	962
	946	1.336	1.743	2.395
1600	677	949	1.240	1.712
	436	606	793	1.099
	1.082	1.526	1.992	2.738
1800	762	1.068	1.395	1.925
	490	682	892	1.236
	1.217	1.717	2.241	3.080
2000	847	1.186	1.550	2.139
	545	758	991	1.374
	1.352	1.908	2.490	3.422
2200	932	1.305	1.705	2.353
	599	833	1.090	1.511
	1.487	2.099	2.739	3.764
2400	1.016	1.423	1.860	2.567
	654	909	1.189	1.648
	1.622	2.290	2.988	4.106
2600	1.101	1.542	2.015	2.781
	708	985	1.288	1.786
	1.758	2.480	3.237	4.449
2800	1.186	1.661	2.170	2.995
	763	1.061	1.387	1.923
	1.893	2.671	3.486	4.791
3000	1.270	1.779	2.325	3.209
	817	1.136	1.487	2.060
	2.028	2.862	3.735	5.133

Højde 500				
Type	11	21	22	33
400	209	286	372	514
	135	183	237	329
	333	461	598	822
500	262	358	465	642
	169	228	297	412
	417	577	747	1.028
600	314	430	557	770
	203	274	356	494
	500	692	896	1.234
700	367	501	650	899
	237	320	415	576
	583	807	1.046	1.439
800	419	573	743	1.027
	270	366	475	659
	666	922	1.195	1.645
900	471	645	836	1.155
	304	411	534	741
	750	1.038	1.345	1.850
1000	524	716	929	1.284
	338	457	593	823
	833	1.153	1.494	2.056
1100	576	788	1.022	1.412
	372	503	653	906
	916	1.268	1.643	2.262
1200	628	859	1.115	1.541
	405	548	712	988
	1.000	1.384	1.793	2.467
1400	733	1.003	1.301	1.797
	473	640	831	1.153
	1.166	1.614	2.092	2.878
1600	838	1.146	1.486	2.054
	541	731	950	1.317
	1.333	1.845	2.390	3.290
1800	942	1.289	1.672	2.311
	608	823	1.068	1.482
	1.499	2.075	2.689	3.701
2000	1.047	1.432	1.858	2.568
	676	914	1.187	1.647
	1.666	2.306	2.988	4.112
2200	1.152	1.575	2.044	2.825
	743	1.005	1.306	1.811
	1.833	2.537	3.287	4.523
2400	1.257	1.719	2.230	3.081
	811	1.097	1.424	1.976
	1.999	2.767	3.586	4.934
2600	1.361	1.862	2.416	3.338
	878	1.188	1.543	2.141
	2.166	2.998	3.884	5.346
2800	1.466	2.005	2.601	3.595
	946	1.279	1.662	2.305
	2.332	3.228	4.183	5.757
3000	1.571	2.148	2.787	3.852
	1.014	1.371	1.780	2.470
	2.499	3.459	4.482	6.168

Varmeydelse i Watt i henhold til EN 442

EN442 (W) 70/40/20°C

EN442 (W) 60/30/20°C

EN442 (W) 75/65/20°C

Højde		600			
Type	11	21	22	33	
400	247	334	430	596	
	160	213	275	382	
	392	538	693	956	
500	309	417	538	745	
	200	266	343	477	
	490	673	866	1.195	
600	371	501	646	894	
	240	319	412	573	
	588	807	1.039	1.433	
700	433	584	753	1.043	
	280	372	481	668	
	686	942	1.212	1.672	
800	495	668	861	1.192	
	320	426	549	764	
	784	1.076	1.386	1.911	
900	556	751	968	1.341	
	360	479	618	859	
	882	1.211	1.559	2.150	
1000	618	835	1.076	1.490	
	400	532	687	955	
	980	1.345	1.732	2.389	
1100	680	918	1.184	1.639	
	440	585	755	1.050	
	1.078	1.480	1.905	2.628	
1200	742	1.001	1.291	1.788	
	480	638	824	1.146	
	1.176	1.614	2.078	2.867	
1400	865	1.168	1.506	2.086	
	560	745	961	1.336	
	1.372	1.883	2.425	3.345	
1600	989	1.335	1.722	2.384	
	640	851	1.099	1.527	
	1.568	2.152	2.771	3.822	
1800	1.113	1.502	1.937	2.682	
	720	958	1.236	1.718	
	1.764	2.421	3.118	4.300	
2000	1.236	1.669	2.152	2.980	
	800	1.064	1.373	1.909	
	1.960	2.690	3.464	4.778	
2200	1.360	1.836	2.367	3.278	
	881	1.170	1.511	2.100	
	2.156	2.959	3.810	5.256	
2400	1.484	2.003	2.582	3.576	
	961	1.277	1.648	2.291	
	2.352	3.228	4.157	5.734	
2600	1.607	2.170	2.798	3.874	
	1.041	1.383	1.786	2.482	
	2.548	3.497	4.503	6.211	
2800	1.731	2.337	3.013	4.172	
	1.121	1.490	1.923	2.673	
	2.744	3.766	4.850	6.689	
3000	1.855	2.504	3.228	4.470	
	1.201	1.596	2.060	2.864	
	2.940	4.035	5.196	7.167	

Højde		700			
Type	11	21	22	33	
400	282	380	487	673	
	182	242	310	429	
	447	612	784	1.085	
500	352	475	608	841	
	228	303	388	536	
	559	765	981	1.356	
600	423	570	730	1.009	
	274	363	465	643	
	670	918	1.177	1.627	
700	493	665	852	1.177	
	319	424	543	750	
	782	1.071	1.373	1.898	
800	564	759	973	1.346	
	365	484	620	857	
	894	1.224	1.569	2.170	
900	634	854	1.095	1.514	
	411	545	698	965	
	1.005	1.377	1.765	2.441	
1000	705	949	1.217	1.682	
	456	605	775	1.072	
	1.117	1.530	1.961	2.712	
1100	775	1.044	1.338	1.850	
	502	666	853	1.179	
	1.229	1.683	2.157	2.983	
1200	846	1.139	1.460	2.018	
	547	726	931	1.286	
	1.340	1.836	2.353	3.254	
1400	986	1.329	1.703	2.355	
	639	847	1.086	1.501	
	1.564	2.142	2.745	3.797	
1600	1.127	1.519	1.947	2.691	
	730	968	1.241	1.715	
	1.787	2.448	3.138	4.339	
1800	1.268	1.709	2.190	3.028	
	821	1.089	1.396	1.929	
	2.011	2.754	3.530	4.882	
2000	1.409	1.899	2.433	3.364	
	912	1.210	1.551	2.144	
	2.234	3.060	3.922	5.424	
2200	1.550	2.089	2.676	3.700	
	1.004	1.331	1.706	2.358	
	2.457	3.366	4.314	5.966	
2400	1.691	2.278	2.920	4.037	
	1.095	1.452	1.861	2.572	
	2.681	3.672	4.706	6.509	
2600	1.832	2.468	3.163	4.373	
	1.186	1.573	2.016	2.787	
	2.904	3.978	5.099	7.051	
2800	1.973	2.658	3.406	4.710	
	1.277	1.694	2.171	3.001	
	3.128	4.284	5.491	7.594	
3000	2.114	2.848	3.650	5.046	
	1.402	1.897	2.388	3.333	
	3.369	4.816	6.226	8.615	

Højde		900			
Type	11	21	22	33	
400	343	467	593	818	
	222	298	377	516	
	544	753	958	1.334	
500	429	584	741	1.022	
	278	372	471	644	
	680	942	1.198	1.667	
600	515	701	889	1.227	
	333	447	565	773	
	816	1.130	1.437	2.000	
700	601	818	1.037	1.431	
	389	521	659	902	
	952	1.318	1.677	2.334	
800	686	935	1.185	1.636	
	444	596	754	1.031	
	1.088	1.506	1.916	2.667	
900	772	1.051	1.334	1.840	
	500	670	848	1.160	
	1.224	1.695	2.156	3.001	
1000	858	1.168	1.482	2.044	
	555	745	942	1.289	
	1.360	1.883	2.395	3.334	
1100	944	1.285	1.630	2.249	
	611	819	1.036	1.418	
	1.496	2.071	2.635	3.667	
1200	1.029	1.402	1.778	2.453	
	667	894	1.130	1.547	
	1.632	2.260	2.874	4.001	
1400	1.201	1.636	2.074	2.862	
	778	1.043	1.319	1.804	
	1.904	2.636	3.353	4.668	
1600	1.373	1.869	2.371	3.271	
	889	1.192	1.507	2.062	
	2.176	3.013	3.832	5.334	
1800	1.544	2.103	2.667	3.680	
	1.000	1.341	1.696	2.320	
	2.448	3.389	4.311	6.001	
2000	1.716	2.337	2.963	4.089	
	1.111	1.490	1.884	2.578	
	2.720	3.766	4.790	6.668	
2200	1.887	2.570	3.260	4.498	
	1.222	1.638	2.072	2.835	
	2.992	4.143	5.269	7.335	
2400	2.059	2.804	3.556	4.907	
	1.333	1.787	2.261	3.093	
	3.264	4.519	5.748	8.002	
2600	2.230	3.038	3.852	5.315	
	1.444	1.936	2.449	3.351	
	3.536	4.896	6.227	8.668	
2800	2.402	3.271	4.149	5.724	
	1.555	2.085	2.637	3.609	
	3.808	5.272	6.706	9.335	
3000	2.645	3.590	4.548	6.348	
	1.666	2.234	2.826	3.866	
	4.080	5.649	7.185	10.002	

Varmeydelse i Watt i henhold til EN 442