

## Novello 8 Ydelsestabel

Beregningfaktor  
per meter radiator  
ved 75/65/20 °C  
i henhold til EN442  
Ligning:  $\phi = K_M \times \Delta T^n$

EN442 (W) 70/40/20°C

EN442 (W) 60/30/20°C

EN442 (W) 75/65/20°C

Højde 300				
Type	11	21	22	33
400	127	185	245	338
	81	119	157	217
	204	298	393	540
500	159	232	306	422
	102	148	196	271
	255	373	491	675
600	191	278	367	507
	122	178	235	326
	305	447	589	809
700	222	325	428	591
	143	207	274	380
	356	522	687	944
800	254	371	489	675
	163	237	313	434
	407	596	786	1.079
900	286	417	551	760
	183	267	352	488
	458	671	884	1.214
1000	318	464	612	844
	204	296	392	543
	509	745	982	1.349
1100	349	510	673	929
	224	326	431	597
	560	820	1.080	1.484
1200	381	556	734	1.013
	244	356	470	651
	611	894	1.178	1.619
1400	445	649	857	1.182
	285	415	548	760
	713	1.043	1.375	1.889
1600	-	742	979	1.351
	-	474	627	868
	-	1.192	1.571	2.158
1800	-	835	1.101	1.520
	-	534	705	977
	-	1.341	1.768	2.428
2000	-	927	1.224	1.689
	-	593	783	1.085
	-	1.490	1.964	2.698
2200	-	1.020	1.346	1.858
	-	652	861	1.194
	-	1.639	2.160	2.968
2400	-	1.113	1.468	2.026
	-	711	940	1.302
	-	1.788	2.357	3.238
2600	-	-	1.591	-
	-	-	1.018	-
	-	-	2.553	-
2800	-	-	1.713	-
	-	-	1.096	-
	-	-	2.750	-
3000	-	-	1.836	-
	-	-	1.175	-
	-	-	2.946	-

Højde 400				
Type	11	21	22	33
400	169	237	310	428
	109	152	198	275
	270	382	498	684
500	212	297	387	535
	136	189	248	343
	338	477	623	856
600	254	356	465	642
	163	227	297	412
	406	572	747	1.027
700	296	415	542	749
	191	265	347	481
	473	668	872	1.198
800	339	474	620	856
	218	303	396	549
	541	763	996	1.369
900	381	534	697	963
	245	341	446	618
	608	859	1.121	1.540
1000	423	593	775	1.070
	272	379	496	687
	676	954	1.245	1.711
1100	466	652	852	1.177
	300	417	545	755
	744	1.049	1.370	1.882
1200	508	712	930	1.284
	327	455	595	824
	811	1.145	1.494	2.053
1400	593	830	1.085	1.498
	381	530	694	962
	946	1.336	1.743	2.395
1600	677	949	1.240	1.712
	436	606	793	1.099
	1.082	1.526	1.992	2.738
1800	762	1.068	1.395	1.925
	490	682	892	1.236
	1.217	1.717	2.241	3.080
2000	847	1.186	1.550	2.139
	545	758	991	1.374
	1.352	1.908	2.490	3.422
2200	-	1.305	1.705	2.353
	-	833	1.090	1.511
	-	2.099	2.739	3.764
2400	-	1.423	1.860	2.567
	-	909	1.189	1.648
	-	2.290	2.988	4.106
2600	-	-	2.015	-
	-	-	1.288	-
	-	-	3.237	-
2800	-	-	2.170	-
	-	-	1.387	-
	-	-	3.486	-
3000	-	-	2.325	-
	-	-	1.487	-
	-	-	3.735	-

Højde 500				
Type	11	21	22	33
400	209	286	372	514
	135	183	237	329
	333	461	598	822
500	262	358	465	642
	169	228	297	412
	417	577	747	1.028
600	314	430	557	770
	203	274	356	494
	500	692	896	1.234
700	367	501	650	899
	237	320	415	576
	583	807	1.046	1.439
800	419	573	743	1.027
	270	366	475	659
	666	922	1.195	1.645
900	471	645	836	1.155
	304	411	534	741
	750	1.038	1.345	1.850
1000	524	716	929	1.284
	338	457	593	823
	833	1.153	1.494	2.056
1100	576	788	1.022	1.412
	372	503	653	906
	916	1.268	1.643	2.262
1200	628	859	1.115	1.541
	405	548	712	988
	1.000	1.384	1.793	2.467
1400	733	1.003	1.301	1.797
	473	640	831	1.153
	1.166	1.614	2.092	2.878
1600	838	1.146	1.486	2.054
	541	731	950	1.317
	1.333	1.845	2.390	3.290
1800	942	1.289	1.672	2.311
	608	823	1.068	1.482
	1.499	2.075	2.689	3.701
2000	1.047	1.432	1.858	2.568
	676	914	1.187	1.647
	1.666	2.306	2.988	4.112
2200	1.152	1.575	2.044	2.825
	743	1.005	1.306	1.811
	1.833	2.537	3.287	4.523
2400	1.257	1.719	2.230	3.081
	811	1.097	1.424	1.976
	1.999	2.767	3.586	4.934
2600	-	-	2.416	-
	-	-	1.543	-
	-	-	3.884	-
2800	-	-	2.601	-
	-	-	1.662	-
	-	-	4.183	-
3000	-	-	2.787	-
	-	-	1.780	-
	-	-	4.482	-

Varmeydelse i Watt i henhold til EN 442

EN442 (W) 70/40/20°C

EN442 (W) 60/30/20°C

EN442 (W) 75/65/20°C

Højde <b>600</b>				
Type	11	21	22	33
<b>400</b>	247	334	430	596
	160	213	275	382
	392	538	693	956
<b>500</b>	309	417	538	745
	200	266	343	477
	490	673	866	1.195
<b>600</b>	371	501	646	894
	240	319	412	573
	588	807	1.039	1.433
<b>700</b>	433	584	753	1.043
	280	372	481	668
	686	942	1.212	1.672
<b>800</b>	495	668	861	1.192
	320	426	549	764
	784	1.076	1.386	1.911
<b>900</b>	556	751	968	1.341
	360	479	618	859
	882	1.211	1.559	2.150
<b>1000</b>	618	835	1.076	1.490
	400	532	687	955
	980	1.345	1.732	2.389
<b>1100</b>	680	918	1.184	1.639
	440	585	755	1.050
	1.078	1.480	1.905	2.628
<b>1200</b>	742	1.001	1.291	1.788
	480	638	824	1.146
	1.176	1.614	2.078	2.867
<b>1400</b>	865	1.168	1.506	2.086
	560	745	961	1.336
	1.372	1.883	2.425	3.345
<b>1600</b>	989	1.335	1.722	2.384
	640	851	1.099	1.527
	1.568	2.152	2.771	3.822
<b>1800</b>	1.113	1.502	1.937	2.682
	720	958	1.236	1.718
	1.764	2.421	3.118	4.300
<b>2000</b>	1.236	1.669	2.152	2.980
	800	1.064	1.373	1.909
	1.960	2.690	3.464	4.778
<b>2200</b>	1.360	1.836	2.367	3.278
	881	1.170	1.511	2.100
	2.156	2.959	3.810	5.256
<b>2400</b>	1.484	2.003	2.582	3.576
	961	1.277	1.648	2.291
	2.352	3.228	4.157	5.734
<b>2600</b>	-	-	2.798	-
	-	-	1.786	-
	-	-	4.503	-
<b>2800</b>	-	-	3.013	-
	-	-	1.923	-
	-	-	4.850	-
<b>3000</b>	-	-	3.228	-
	-	-	2.060	-
	-	-	5.196	-

Højde <b>700</b>				
Type	11	21	22	33
<b>400</b>	282	380	487	673
	182	242	310	429
	447	612	784	1.085
<b>500</b>	352	475	608	841
	228	303	388	536
	559	765	981	1.356
<b>600</b>	423	570	730	1.009
	274	363	465	643
	670	918	1.177	1.627
<b>700</b>	493	665	852	1.177
	319	424	543	750
	782	1.071	1.373	1.898
<b>800</b>	564	759	973	1.346
	365	484	620	857
	894	1.224	1.569	2.170
<b>900</b>	634	854	1.095	1.514
	411	545	698	965
	1.005	1.377	1.765	2.441
<b>1000</b>	705	949	1.217	1.682
	456	605	775	1.072
	1.117	1.530	1.961	2.712
<b>1100</b>	775	1.044	1.338	1.850
	502	666	853	1.179
	1.229	1.683	2.157	2.983
<b>1200</b>	846	1.139	1.460	2.018
	547	726	931	1.286
	1.340	1.836	2.353	3.254
<b>1400</b>	986	1.329	1.703	2.355
	639	847	1.086	1.501
	1.564	2.142	2.745	3.797
<b>1600</b>	1.127	1.519	1.947	2.691
	730	968	1.241	1.715
	1.787	2.448	3.138	4.339
<b>1800</b>	1.268	1.709	2.190	3.028
	821	1.089	1.396	1.929
	2.011	2.754	3.530	4.882
<b>2000</b>	1.409	1.899	2.433	3.364
	912	1.210	1.551	2.144
	2.234	3.060	3.922	5.424
<b>2200</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>2400</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>2600</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>2800</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>3000</b>	-	-	-	-
	-	-	-	-
	-	-	-	-

Højde <b>900</b>				
Type	11	21	22	33
<b>400</b>	343	467	593	818
	222	298	377	516
	544	753	958	1.334
<b>500</b>	429	584	741	1.022
	278	372	471	644
	680	942	1.198	1.667
<b>600</b>	515	701	889	1.227
	333	447	565	773
	816	1.130	1.437	2.000
<b>700</b>	601	818	1.037	1.431
	389	521	659	902
	952	1.318	1.677	2.334
<b>800</b>	686	935	1.185	1.636
	444	596	754	1.031
	1.088	1.506	1.916	2.667
<b>900</b>	772	1.051	1.334	1.840
	500	670	848	1.160
	1.224	1.695	2.156	3.001
<b>1000</b>	858	1.168	1.482	2.044
	555	745	942	1.289
	1.360	1.883	2.395	3.334
<b>1100</b>	944	1.285	1.630	2.249
	611	819	1.036	1.418
	1.496	2.071	2.635	3.667
<b>1200</b>	1.029	1.402	1.778	2.453
	667	894	1.130	1.547
	1.632	2.260	2.874	4.001
<b>1400</b>	1.201	1.636	2.074	2.862
	778	1.043	1.319	1.804
	1.904	2.636	3.353	4.668
<b>1600</b>	1.373	1.869	2.371	3.271
	889	1.192	1.507	2.062
	2.176	3.013	3.832	5.334
<b>1800</b>	1.544	2.103	2.667	3.680
	1.000	1.341	1.696	2.320
	2.448	3.389	4.311	6.001
<b>2000</b>	1.716	2.337	2.963	4.089
	1.111	1.490	1.884	2.578
	2.720	3.766	4.790	6.668
<b>2200</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>2400</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>2600</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>2800</b>	-	-	-	-
	-	-	-	-
	-	-	-	-
<b>3000</b>	-	-	-	-
	-	-	-	-
	-	-	-	-

Varmeydelse i Watt i henhold til EN 442